

Data Format



Data followed by <Enter>
(Default)



No message after data



Data followed by <Enter>
+ new line



Data followed by new line



Data followed by TAB

Características estandar de fábrica

Parameter	Default
Baud Rate	115200 BPS
Word Format	None, 8, 1
Word Format	None, 8, 1
Illumination	On
LED-Good Read	On
Number of Beep-Good Read	1
Good Read Delay	200
Same Code Delay	500ms
Scan Mode	Manual Trigger
Manual Mode	30000ms
Presentation	500ms
Centering Windows	Off
Ship Image	JPG/BMP
No Read	Off
Image Reverse	Off
Data Redundant	Off

System Settings



Reset to Factory Default

Scan Mode



Trigger Mode



Auto Scan Mode



LECTOR DE CÓDIGOS DE BARRA Guía de usuario *Lector Posline SC2135*

Symbologies



Enable CODE39



Disable CODE39



Enable EAN13



Disable EAN13



Enable CODE128



Disable CODE128



Enable QR Code



Disable QR Code



Enable CODE93



Disable CODE93



Enable Codabar



Disable Codabar



Code 128 Code Page: Binary



Enable PDF417



Disable PDF417



Enable MSI



Disable MSI



Code 39 Code Page: Binary



Enable Chinese Post Code



Disable Chinese Post Code

Symbologies

Spanish Keyboard

Enable Spanish keyboard layout in USB HID interface. please scan all 3 barcode below to complete the settings.